



KHDT

PVC Single Sided Foam Tape - Hard, White, Fire Retardant Waterseal to BS 476 Part 6 and Part 7 Class 1

DESCRIPTION

KHDT is primarily a foam compression sealant. The product is white. The foam is hard and predominantly closed celled. An acrylic pressure sensitive adhesive is coated on one side. The product has a paper release liner on the non-adhesive face. KHDT is a water, air and dust seal when compressed.

APPLICATIONS

- Forms a compression water seal.
- For preventing electrolytic corrosion.
- For cushioning and gap filling.
- For heavier duty applications.
- Forms a compression air/ dust seal.

PRODUCT FEATURES

- Minimum 30% compression required to effect a water seal.
- Service temperature: -30°C to +70°C.
- Application temperature: +10°C to +40°C.
- Exhibits a high degree of flame retardancy.
- Shelf life of 1 year from date of dispatch.
- Coated on one side with a high quality pressure sensitive, fire retardant acrylic adhesive.
- Good resistance to dilute acids and alkalis.
- Paper release liner on the non-adhesive face, reducing dimensional change during application.
- Very good ultraviolet {UV} light resistance.
- Resistance to abrasion, corrosion and moisture.
- Suitable for indoor and outdoor environments.
- No known hazards associated with this product.
- Pre-determined dimensional sealant reduces waste.
- Clean to use/ clean edge finish.

STANDARD PRESENTATIONS

- Core: 76mm plastic
- Formats: Logs; Rolls; Spools
- Thickness : 4.5 mm

ACCREDITATION

Fire rated to BS 476 Part 6: 1989 + A1: 2009 (R2015) - fire propagation Part 7: 1997 Ckus 1 - surface spread of flame.

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the shelf life of the tape is 12 months from the date of dispatch. Surfaces should be clean, dry and free of dust, grease, oil or other contaminants. Customers are recommended to make their own assessment of our products under their own conditions, for their own requirements.



佳恒冷氣工程有限公司
Kai Hang Air-Cond. Eng Co. Ltd

香港新界葵涌葵豐街41-45號安福工業大廈16樓H室
Block H, 16/F, On Fook Industrial Building,
41-45 Kwai Fung Crescent, Kwai Chung, N.T., Hong Kong
Fax: (852) 3171 7810 Phone: (852) 3171 7781, 3172 1073

**TECHNICAL
DATA**



KHDT

PVC SINGLE SIDED FOAM TAPE-HARD

	54	White
	9mm	Blanc Weiss
	15m	Bianco
	4.5mm	Blanco

Gross Weight: 10.8kg(Each Box) **Net Weight: 13.4kg**(Each Box)